

IOT SMART HOME DOOR CAMERA

KC-S81MPOE NEW

PRODUCT FUNCTION

- Metal body
- 1 Mega pixel
- White LED for visotor recognition at night
- Call and video communication with Monitor
- Doorlock interface

SPECIFICATIONS

Power source	PoE DC48V (IEEE 802.3af)
Power consumption	3W(Max)
Wiring	LAN: UTP Cat 5e or higher
Body material	Metal A/L
Mount type	Surface mount
Camera angle	Diagonal 110°
Min. Illumination	0.1 lux(LED ON)
Dimesion	70(W) x 125(H) x 21(D)mm

MAKING YOUR HOME MORE CONVENIENT AND SAFER

KOCOM Home APP

DEVICE CONTROL

Smart devices linked to the app can be easily controlled and managed with one app.

SMART CALL

It is possible to receive calls from visitors anytime, anywhere on your smartphone and make video communication.

SMART DOOR OPEN

Even if you are outside, you can check visitors through the app and open the door.

'KOCOM Home' APP

IOT SMART HOME IP VIDEO PHONE

KCV-S701IPOE NEW

BLACK WHITE

PRODUCT FUNCTION

- 7" Full touch color LCD Monitor
- Applied graphic user interface(GUI)
- Fully digital system
- Answer the door from anywhere with mobile app(KOCOM Home)
- Power over ethernet(PoE)
- Expandible up to 4 monitors, 2 door cameras and 2 CCTV cameras
- Auto still image capture(MAX. 50 cuts)\
- 'DO NOT DISTURB' and 'ABSENT MODE' available
- Share access

SPECIFICATIONS

Display	7 inch Color LCD
Power source	PoE DC48V (IEEE 802.3af)
Power consumption	3W(±20%)(on Stand by), 7W(±20%)(Full load)
Wiring	LAN: UTP Cat 5e or higher
Mount type	Surface Mount
Dimension	197(W) x 176(H) x 23(D) mm

WIRING DIAGRAM

