ELECTROMAGNETIC DOOR HOLDER





Features

LOW PROFILE CONSTRUCTION
VARIETY HOLDING FORCE AVAILABLE
INTERGRATED RELEASE SWITCH
12/24Vdc & 230Vac
ADJUSTABLE KEEPER PLATE
TOP & REAR CABLE ENTRY
AC VERSION FITTED WITH POWER FUSE
RESIDUAL MAGNETISM RELEASE PIN
CE Marked

Description

The new KAWAPI range of door retainers is ideally suited to applications where maximum protection is needed against vandalism or mechanical damage. Each model features a rugged plastic housing, a holding magnet with integral ejection pin and a manual release switch.

Holding Force

With its high holding force (up to 60kg), is particularly useful in industrial applications where normal holding forces are inappropriate.

Dimension

105mm(W) x 105mm (H) x 50mm (D)

Door Holder Accessories







Specification	DC Version	า		AC Version			
Model No.	KP-304-S25	KP-304-S60	KP-304-S50	KP-304-S40	KP-304-AC40	KP-304-AC20	KP-304-AC11
Electrical Supply:	12V DC	24V DC	24V DC	24V DC	230V AC	230V AC	230V AC
Current Consumption:	40mA	60mA	60mA	60mA	8mA	8mA	8mA
Holding Force (Kg/Newton):	25kg/250N	60kg/600N	50kg/500N	40kg/400N	40kg/400N	20.5kg/200N	11.5kg/100N
Release Switch:	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Ingress Protection:	IP51	IP51	IP51	IP51	IP51	IP51	IP51
Keeper Adjustment:	90°	90°	90°	90°	90°	90°	90°
Operating Temp:	-10° to +55°C	-10° to +55°C	-10° to +55°C	-10° to +55°C	-10° to +55°C	-10° to +55°C	-10° to +55°C
Weight(per unit):	644gm/699gm	676gm/731gm	649gm/704gm	644gm/699gm	710gm/762gm	710gm/762gm	710gm/762gm
Colour:	White	White	White	White	White	White	White
Housing:	ABS	ABS	ABS	ABS	ABS	ABS	ABS
Ordercode:	3304-2512	3304-0600	3304-0500	3304-0400	3304-AC40	3304-AC20	3304-AC11

Distributed by

