# Intelligent Wi-fi 1080P IP Camera MS-ZND1247AP-W





#### **Superior Image Quality**

- 1/2.9" 2235 low illumination CMOS sensor
- Full HD 1080P 25fps/30fps image
- Wide Dynamic Range, up to 80db, ensures glare-free images
- Excellent performance in extra low lux condition with 3D noise reduction

### **Solution-Oriented Design**

- 3.6mm lens
- 12 Black Tech IR Leds, up to 20m distance at night
- H.265 codec, supports main stream and extra stream
- Compatible with third-party equipments based on Onvif 2.4

#### **Easy Installation and Use**

- Ceilling mount and wall mount are adaptable.
- User-friendly software and mobile app, enables remote configuration and viewing through CMS or MEESO mobile app.

## **MS-ZND1247AP-W Network Camera**

Camera	
Sensor	1/2.9" 2235 CMOS sensor
Processor	Embedded RTOS, dual-core 32-bit DSP (Hi3516C V300)
Lens	3.6mm
Day & Night	Dual Optical Filters, Day/Night modes auto switch
IR LED	12 4th-Generation IR LEDs, IR range 25M
Minimum Illumination	color 0.01Lux@F1.2 black/white 0.001Lux@F1.2
Shutter Speed	1/50(1/60)s to 1/10,000s
Motion Detection	Up to 4 area
Privacy Masking	Up to 4 area
Video	
Video Compression	H.265, support dual stream, AVI; 0.1M~8Mpbs variable
Resolutions	2 Megapixel, 1920*1080
Frame Rate	1~30f/s variable
Dual stream	Main Stream 2Mbps~6Mbps Sub Stream 512kbps~2.5Mbps (adjustable)
Image Settings	AE Reference, BLC, White Balance, DWDR, AGC
Snapshot	JPEG format
Noise Reduction	2D/3D-NR
AGC & WB & Exposure	Auto Gain Control, Auto White Balance, Auto Exposure
Audio	
Audio Input/Output	Audio 1 in/0 out
Alarm	
Alarm Input/Output	Optional, could be extended to alarm 0 in/1 out (MS-ZND1247AP-WAA)

Network		
Network Protocol	RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP etc	
Safety	Password protection	
Water Mark	Support	
Wifi	Support	
SD card	Support (64G at max)	
Compatibility	Onvif 2.4	
Max. User Acess	10 users	
Mobile Devices	Xmeye for Iphone & Android devices	
System Integration		
Analytics	Motion detection, Support for MEESO camera application platform enabling installation of third-party application. Line/Area cross detection, Object missing detection, illegal parking detection.	
Alarm Event	Motion Detect, Video Loss, Video Cover, Network Abnormal	
Data Streamii	n Event data	
Alarm Responses	Snapshot, Email Alert, Start to Record , FTP Upload	
Environmental		
Temperature	-30℃~60℃	
Humidity	< 95% (No condensing)	
IP rate	IP65	
Vandal Resist	a /	
General		
Casing	Superior aluminum alloy, Good cooling effect	
Dimension		
Weight	Around 1KG	
Power (POE)	Optional	
Connectors	RJ45; DC	
Languages	English, Spanish, German, French, Italian, Russian, Japanese, Korean, Portuguess, Greek, Turkish, Polish, Roman, Arabic, Indonesian, Swedish, Czech,	

Bulgarian, Slovakia, Chinese

For more information please contact Email: marketing@meeso.cn

TEL: +86-755-36622324 Web: www.meeso.cn



Meeso Communications reserves the right to make changes in products design or specifications without notification.

