


PXR-10 / 12 EM Reader



PXR-10



PXR-12

Features

- Stylish and slim appearance design with tempered glass material, combines high-tech, security and aesthetic appearance. Looks great to match with modern interior decoration.
- Supports EM card (125 KHz)
- Read range is around 4 cm.
- Provides different communication interfaces (Wiegand or RS-485) for choice to work with controllers.
- Provides RS-485 communication interface to suit for long distance installation(PXR-10/12 ES).
- Wide operation temperature range; It can be installed in extreme cold or hot regions.
- Case sensor detection function.
- Watchdog function secures system free from halting.
- Wall-embedded design and two dimensions are available for different market requirements : PXR-12 for US market and PXR-10 for European market.

Ordering Information

Package Content: <ul style="list-style-type: none"> • PXR-10 x 1 • Quick Start Guide x 1 • Accessory Pack x 1 	
Model No. Identification PXR-10EW 	Color Black (BL)

Specification

Model No.	PXR-10EW	PXR-10ES	PXR-12EW	PXR-12ES
Read Format	EM (125 KHz)			
Read Range	4 cm			
Comm. Interface	Wiegand	RS-485	Wiegand	RS-485
Input Port	Case Sensor x 1			
ID Setting	None	DIP switch	None	DIP switch
Comm. Baudrate	N/A	19,200 bps-N-8-1	N/A	19,200 bps-N-8-1
LED Indicator	Green / Red Bi-color LED x 1 (Status / Power)			
Beep Tone	Buzzer			
Power Input	DC 12V / 1A			
Current Consumption	300mA (max)			
Operating Temp.	-40°C~ 70°C / -40°F~ 158°F			
Relative Humidity	20% ~ 80%(Non-condensing)			
Dimensions (LxWxH)(mm)	PXR-10 (for European market) Faceplate : 86(L) x 86(W) x 9(H)(mm) Backside box : 52(L) x 58(W) x 24(H)(mm) PXR-12 (for US market) Faceplate : 120(L) x 75(W) x 9(H)(mm) Backside box : 70(L) x 42(W) x 26(H)(mm)			